

HYDRAULIC PUMP DRIVE QUICK SELECTION GUIDE

MODEL	HP @ 2500 rpm	MAX TORQUE lb. ft.	FLYWHEEL HOUSING SIZE	RATIOS (all increasing and decreasing, unless noted as INC or DEC)	PUMP CENTER DISTANCE (VERTICAL x HORIZONTAL)
1751D	460	966	1,2,3,4,5	DIRECT 1:1	N/A
751DC	460	966	1,2,3,4	DIRECT 1:1	N/A
1PD06	495	1,040	1,2,3,4	1:1, 1.18, 1.25, 1.32, 1.40, 1.48, 1.57, 1.67	6.00
2PD06	495	1,040	1,2,3,4	1:1, 1.18, 1.25, 1.32, 1.40, 1.48, 1.57, 1.67	12.00
2PD08	725	1,525	1,2,3,4	1:1, 1.23, 1.34, 1.40, 1.53 INC	16.00
2PD10	950	1,995	1,2,3,4	1:1, 1.21, 1.29, 1.38	21.00
3PD06	495	1,040	1,2,3,4	1:1, 1.17, 1.29, 1.36, 1.52 INC	8.49 X 12.38
3PD08	725	1,525	1,2,3,4	1:1, 1.23, 1.34, 1.40, 1.53 INC	13.29 X 12.00
3PD10	950	1,995	1,2,3,4	1:1, 1.21, 1.29, 1.38	15.91 X 18.00
4PD08	725	1,525	1,2,3,4	1:1, 1.23, 1.34, 1.40, 1.53 INC	11.08 X 11.54
4PD09	815	1,710	1,2,3,4	1:1, 1.20, 1.30, 1.40	12.18 X 13.26
4PD11	1,025	2,150	1,2,3,4	1:1, 1.16, 1.31, 1.39	16.06 X 16.00
KJ67 (5 pad)	950	1,995	0,1,2	1:1, 1.18, 1.39	16.00
806 (6 pad)	600	1,260	1,2,3	1.43 INC, 1.68 INC Dual Ratios (1.31 INC, 1.68 INC)	10.03 X 11.85 (16.82, 40.52)

Note: Refer to warning, safety, and installation manual before installing or operating power transmission products.

Contact Us for Installation Manuals.